

# GRNLED

GOLUMEN® EuroLight

**PRODUCT ALBUM**



## BROCHURE

By Greenriy Technology Co., Limited

## CONTENT



**01** PAGE

Led Track Lighting



**02/04** PAGE

Magnetic Track Lighting System



**05** PAGE

Weather led batten/ T8 LED Tube



**06** PAGE

LED Panel light/Waterproof Panel light



**07** PAGE

Linear LED lighting



**08/17** PAGE

Recessed downlight/Waterproof downlight/Surface downlight



**18** PAGE

Highbay LED Lighting



**19** PAGE

Solar led Street Light/Solar Floodlight



**20/21** PAGE

Led Streetlight



**22/23** PAGE

LED Floodlight



**24/29** PAGE

Wall Light/Outdoor Spotlight/ Inground Light/ Bollard Light...

# PROFILE

Greenriy Technology Co.,Limited/Shenzhen Gelvmei Technology Co.,Ltd with brand GRNLED, GOLUMEN, and EuroLight which is especially for Nigeria Market is a professional manufacturer, factory, supplier of Led lights. Established in 2014 at Shenzhen city in China, has grown from its humble origins into an lighting industry leader and the best manufacturer and supplier. By focusing on advanced led technologies and outstanding talent, GRNLED offers professionals and users the solutions and support their need for a wide variety of applications. Our production capacity up to 10000pcs/days for common standard lighting. We pursue the following company culture to create the greatest value for customers

**Honesty:**Honesty is the most basic of our company.It's the most important culture. All products are free from fraud.**Innovation:**Continuously develop and research new LED products,to meet the innovative requirements of customers.**Precisseness:**On the basis of innovation, and at the same time with a rigorous attitude to do a good job in every process of the product. Ensure that every product is in line with customer requirements and market requirements.

## WHY US

- **Certification:** ISO9001:2015 listed. And all products are are CE Certified, RoHS Compliant.
- **One-stop supply:** Mostly all types led lights we can produce.
- **Better price:** Our led lamps are 10%-30% cheaper than other suppliers on the market.
- **OEM ODM Service:** Accept OEM ODM for different items.
- **Faster delivery:** Delivery time is fastest, some items is only 1-3days.
- **Quality Control:** Each lights will be 8-12hours age test before sent out.

## WARRANTY

The basic warranty periods for our led lights is 2-3years, and 5years .

- During guarantee periods, GRNLED provide following supports
- We can send FREELY new products or spares to you if there is any quality issues caused by us within guarantee periods, and the freight charge will be paid by our factory.
- Out of warranty period, It is ok for us to provide extra spares, but all expense for repair and shipping cost should be paid by customers.

## PARTNERS

BRIDGELUX

MW  
MEAN WELL

LIFUD

CREE

MOSO<sup>®</sup>

DONE<sup>®</sup>

EUCHIPS

EAGLE RISE

PHILIPS

OSRAM


BOKE

...

GRNLED Quality creates customer awariness and conscious customers create quality  
LED LIGHT MANUFACTURER



LED Track Lighting Series



**Hot Sale Track Light**

Track head: 2wires/3wires/4wires  
 Source: Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, isolated driver 2/3/5years warranty

Order Model	GR-TL-10WA-01	GR-TL-20WA-01	GR-TL-30WA-01	GR-TL-35WA-01
Power	10W±5%	20W±5%	30W±5%	35W±5%



**Commercial Track Light**

Track head: 2wires/3wires/4wires  
 Source: Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/EUCHIPS/BOKE,3/5years warranty

Order Model	GR-TL-10WA	GR-TL-15WA	GR-TL-20WA	GR-TL-30WA
Power	10W±5%	15W±5%	20W±5%	30W±5%



**Adjustable beam Track Light**

Adjustable beam angle from 15° to 60°  
 Track head: 2wires/3wires/4wires  
 Source: Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/EUCHIPS/BOKE,3/5years warranty

Order Model	GR-TL-10WD	GR-TL-20WD	GR-TL-30WD
Power	10W±5%	20W±5%	30W±5%



Order Model	Power Watt
GR-TL-20WF	20W±5%
GR-TL-30WF	30W±5%



Order Model	Power Watt
GR-TL-20WB	20W±5%
GR-TL-30WB	30W±5%

**Track Rail & Accessories**



Which kind of track do you need ?




2 wires Track




3 wires Track



4 wires Track




6 wires Track



### Classic Magnetic Track

Color body: Black/ White  
 Track width: 20mm & 35mm optional  
 Conductor: 4 wires pure copper conductor  
 Compatible: yes, compatible for all magnetic light on markets / 1000mm/2000mm/3000mm length available



### 4 IN 1 Magnetic Track



One track can be compatible with surface, recessed, trimless, pendant installation by extra accessories. 1000mm/1500mm/2000mm /3000mm length available





## Feature

- DC48V Input / AC220V Input optional
  - 20MM/35MM Width Track optional
  - Triac dimmable/ 0-10V/DALI Dimmable/ Zigbee smart 3CCT+Dim solution+ Remote control
- Working with Google Home, Amazon Alexa smart speaker and TUYA APP.



### ■ Magnetic Grille Light

DC48V 24°; Black/white finished; 2/3/5 Years warranty

Order Model	GR-ML-6WGS	GR-ML-12WGS	GR-ML-18WGS	GR-ML-24WGS	GR-ML-30WGS
Wattage	6W	12W	18W	24W	30W
Size(mm)	L112*W22/35	L220*W22/35	L328*W22/35	L435*W22/35	L543*W22/35



### ■ Magnetic Linear Light

DC48V 120°; Black/white finished; 2/3/5 Years warranty

Order Model	GR-ML-10WML	GR-ML-20WML	GR-ML-30WML	GR-ML-40WML
Wattage	10W	20W	30W	40W
Size(mm)	L300*W22/35	L600*W22/35	L900*W22/35	L1200*W22/35



### ■ Magnetic Spot Light

DC48V 24°; Black/white finished; 2/3/5 Years warranty

Order Model	GR-ML-10WTL	GR-ML-15WTL	GR-ML-20WTL	GR-ML-30WTL
Wattage	10W	15W	20W	30W
Size(mm)	Φ47*100mm	Φ57*140mm	Φ67*150mm	Φ70*150mm



### ■ Magnetic Fold Light

DC48V 24°; Black/white finished; 2/3/5 Years warranty

Order Model	GR-ML-6WFS	GR-ML-12WFS	GR-ML-18WFS
Wattage	6W	12W	18W
Size(mm)	L118*W22/35	L230*W22/35	L338*W22/35



20W L-Shape linear Lights



10W Magnetic Ball Light



5W Magnetic Pendant Light

## SURFACE MAGNETIC TRACK SYSTEM

**MAGNETIC**  
ATTRACTION ORBIT

Ultra-thin Track  
0.5cm



### ■ Magnetic Linear Light

Model	GR-ML-12WML-03	GR-ML-24WML-03	GR-ML-36WML-03
Wattage	12W	24W	36W
Size(mm)	L370*W34*H32mm	L675*W34*H32mm	L975*W34*H32mm



### ■ Magnetic Grille Light

Model	GR-ML-10WGS-03	GR-ML-20WGS-03	GR-ML-30WGS-03
Wattage	10W	20W	30W
Size(mm)	L304*W34*H33mm	L600*W34*H32mm	L856*W34*H32mm



### ■ Magnetic Fold Light

Model	GR-ML-6WFS-03	GR-ML-12WGS-03	GR-ML-18WGS-03	GR-ML-24WFS-03
Wattage	6W	12W	18W	24W
Size(mm)	L128*W34*H60mm	L237*W34*H60mm	L344*W34*H60mm	L452*W34*H60mm



### ■ Magnetic Spot Light

Model	GR-ML-10WTL-03	GR-ML-15WTL-03	GR-ML-20WTL-03	GR-ML-30WTL-03
Wattage	10W	15W	20W	30W

DC48V input; Black/White finished, 24° beam angle, 50000hrs lifetime.



### ■ Magnetic Cylinder Light

Model: GR-ML-10WCL  
DC48V input 24° Black/white finished

## ■ ACCESSORIES







### ■ Top Weatherproof led batten

Beam angle: 120°; PC Bottom+PC Cover

Source: Osram/Bridgelux SMD CRI80 100-129lm/w

Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-TPS-2F10WB	GR-TPD-2F20WB	GR-TPS-4F20WB	GR-TPD-4F40WB	GR-TPS-5F30WB	GR-TPD-5F50WB
Wattage	10W	20W	20W	40W	30W	50W
Size(mm)	L600*W82*H72	L600*W82*H72	L1200*W82*H72	L1200*W82*H72	L1500*W82*H72	L1500*W82*H72




### ■ Weatherproof led batten with T8 LED Tube

Beam angle: 120°; ABS Bottom+PC cover

Source: T8 led tube light 100-120lm/w

Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-TPS-2F9WA	GR-TPD-2F18WA	GR-TPS-4F18WA	GR-TPD-4F36WA	GR-TPS-5F22WA	GR-TPD-5F44WA
Wattage	9W	9W*2	18W	18W*2	22W	22W*2
Size(mm)	L665*W75*H86	L665*W113*H86	L1265*W75*H86	L1265*W113*H86	L1565*W75*H86	L1565*W113*H86





### ■ New Weatherproof led batten

Beam angle: 120°; IP65

Source: Osram/Bridgelux SMD CRI80 100-129lm/w

Driver: 110/220-240VAC 50/60Hz; PF>0.9; constant current driver, only 2/3years warranty

Order Model	GR-TPP-600	GR-TPP-1200	GR-TPP-1500
Wattage	18W	36W	48W
Size(mm)	L600*W65*H42	L1200*W65*H42	L1500*W65*H42



Model	Length	Wattage
GR-T5-600	600mm	9W
GR-T5-1200	1200mm	18W
GR-T5-1500	1500mm	22W



Model	Length	Wattage
GR-T8600-9W	600mm	9W
GR-T81200-18W	1200mm	18W
GR-T81500-22W	1500mm	22W




Model	Length	Wattage
GR-DF-600A	600mm	18W
GR-DF-1200A	1200mm	36W
GR-DF-1500A	1500mm	44W



# LED LIGHT PANEL


CE RoHS



Surface frame



ropes



## Edeg-lit Panel Light

Beam angle: 120°, white/silver finished optional. IP22  
 Source: Epistar/Samsung SMD CRI80 100-129lm/w. PMMA LGP  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty




Order Model	GR-PL3030-18W	GR-PL6060-40W	GR-PL12030-40W	GR-PL12060-50W
Wattage	18W	40W	40W	50W
Size(mm)	295*295*9	595*595*9	1195*295*9	1195*595*9mm



## Back-lit Panel Light

Beam angle: 120°, white finished. IP22  
 Source: Epistar SMD CRI80 100-129lm/w.  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty




Order Model	GR-PL3030-18WD	GR-PL6030-20WD	GR-PL6060-40WD	GR-PL12030-40WD	GR-PL12060-72WD
Wattage	18W	20W	40W	40W	72W
Size(mm)	295*295*33	595*295*33	595*595*33	1195*295*33	1195*595*33



## Waterproof LED Panel Light

Beam angle: 120°, white finished. IP65  
 Source: Epistar SMD CRI80 100-120lm/w.  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-PL3030-18WF	GR-PL6030-20WF	GR-PL6060-40WF	GR-PL12030-40WF	GR-PL12060-72WF
Wattage	18W	20W	40W	40W	72W
Size(mm)	295*295*31	595*295*31	595*595*31	1195*295*31	1195*595*31





### ■ Continuous Pendant Linear Light

Beam angle: 120°, white/black finished optional  
 Source: Osram/Bridgelux SMD CR180 100-129lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-LS5070-1200	GR-LS5070-1500	GR-LS5070-2400	GR-LS5050-1200	GR-LS5050-1500	GR-LS5050-2400
Wattage	40W	48W	72W	36W	48W	72W
Size(mm)	L1200*W50*H70	L1500*W50*H70	L2400*W50*H70	L1200*W50*H50	L1500*W50*H50	L2400*W50*H50



### ■ Continuous Recessed Linear Light

Beam angle: 120°, white/black finished optional  
 Source: Osram/Bridgelux SMD CR180 100-129lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-LS5035-1200	GR-LS5035-1500	GR-LS5035-2400	GR-LS6535-1200	GR-LS6535-1500	GR-LS6535-2400
Wattage	36W	48W	72W	36W	48W	72W
Size(mm)	L1200*W50*H35	L1500*W50*H35	L2400*W50*H70	L1200*W65*H35	L1500*W65*H35	L2400*W65*H35
Outcut(mm)	L1190*W42*H65	L1490*W42*H65	L2390*W42*H65	L1190*W52*H65	L1490*W52*H65	L2390*W52*H65



### ■ Supermarket pendant light


Beam angle: 24°+ 120°, adjustable  
 Source: Osram/Bridgelux SMD CR180 100-129lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-LS-120W
Wattage	120W
Size(mm)	L1100*W155*H55



### High Power pendant light

Model: GR-LS5071-1200  
 Power: 80W for 1200mm length  
 60°; continuous connection



### Small aluminum profile

small aluminum profile with led flexible strip lights, DC24V, application for different commercial projects



### Combined pendant lamp

Model: GR-LS6633-36W  
 Size: L1065\*W33\*H66mm



### Hot Sale downlight



Source: Osram/Bridgelux SMD CR182 100lm/w  
Beam angle: 90°, UGR<15

Driver: 110/220-240VAC 50/60Hz; LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty

Order Model	GR-DL-7WA	GR-DL-9WA	GR-DL-12WA	GR-DL-15WA	GR-DL-18WA	GR-DL-24WA	GR-DL-30WA
Size	Ø79*36	Ø93*H45	Ø112*H52	Ø135*H60	Ø162*H72	Ø192*H83	Ø225*H97
Outcut	Ø65-70	Ø75-80	Ø95-100	Ø115-120	Ø140-145	Ø170-175	Ø195-205



### Top Grade COB downlight



Source: Osram/Bridgelux COB CR192 100lm/w  
Beam angle: 24/36/60°, UGR<15

Driver: 110/220-240VAC 50/60Hz; LiFud/Osram/Philips/Boke/Eagleries 5Years warranty

Order Model	GR-DL-10WS	GR-DL-15WS	GR-DL-20WS	GR-DL-30WS	GR-DL-40WS	GR-DL-50WS	GR-DL-60WS
Size	Ø79*36	Ø93*H45	Ø112*H52	Ø135*H60	Ø162*H72	Ø192*H83	Ø225*H97
Outcut	Ø65-70	Ø75-80	Ø95-100	Ø115-120	Ø140-145	Ø170-175	Ø195-205



### Commercial Led Downlight (10inch)



Beam angle: 120° for SMD; 60° for COB

Source: Osram/Bridgelux SMD CRI82/COB CRI90, 100lm/w

Driver:110/220-240VAC 50/60Hz,LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty

Order Model	GR-DL-15WN	GR-DL-20WN	GR-DL-30WN	GR-DL-40WN	GR-DL-40WN	GR-DL-50WN
Size(mm)	Ø145*H60	Ø160*H60	190*H60	Ø230*H75	Ø250*H75	Ø300*H110
Outcut(mm)	Ø120-125	Ø140-145	Ø165-170	Ø205-210	Ø210-230	Ø240-280



### Adjustable Deep downlight



Source: Osram/Bridgelux COB CRI92

Beam angle: 15/24/36°, UGR<10

Driver:110/220-240VAC 50/60Hz,LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty

Order Model	GR-DL-10WG-03	GR-DL-15WG-03	GR-DL-20WG-03	GR-DL-30WG-03	GR-DL-40WG-03	GR-DL-50WG-03
Size(mm)	Ø90*H115	Ø110*H115	Ø110*H115	Ø140*H162	Ø160*H162	Ø160*H162
Outcut(mm)	Ø75	Ø95	Ø95	Ø120-125	Ø140-145	Ø140-145

### Popular Low glare Downlight



Beam angle:15/24/36/60°.

Source: Osram/Bridgelux COB CRI92 100lm/w

Reflector:White/Black/Silver/Gold reflector optional. UGR<15

Driver:LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty

Order Model	GR-DL-5WA-02	GR-DL-7WA-02	GR-DL-10WA-02	GR-DL-12WA-02	GR-DL-15WA-02	GR-DL-20WA-02	GR-DL-25AW-02	GR-DL-30WA-02	GR-DL-40AW-02
Size(mm)	Ø60*H35	Ø85*H45	Ø90*H47	Ø105*H50	Ø130*H52	Ø160*H60	Ø175*H63	Ø175*H63	Ø220*H75
Outcut(mm)	Ø55	Ø75	Ø95	Ø80	Ø120	Ø145	Ø160	Ø160	Ø205

### Anti glare Led Downlight



Source: Osram/Bridgelux SMD or COB CRI90

Beam angle: 60/90°, URG<13

Driver:110/220-240VAC 50/60Hz.LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty

Order Model	GR-DL-9WR	GR-DL-12WR	GR-DL-15WR	GR-DL-20WR	GR-DL-25WR	GR-DL-30WR	GR-DL-40WR
Size(mm)	Ø100*H75	Ø120*H75	Ø145*H80	Ø170*H80	Ø190*H85	Ø230*H90	Ø230*H90
Outcut(mm)	Ø75	95	Ø120	Ø155	Ø175	Ø205	Ø205

### Top Led Downlight



Beam angle: 60°

Source: Osram/Bridgelux SMD CRI82/COB CRI90, 100lm/w

Driver:110/220-240VAC 50/60Hz,LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty

Order Model	GR-DL-10WM	GR-DL-15WM	GR-DL-20WM	GR-DL-25WM	GR-DL-30WM
Size(mm)	Ø110*H75	Ø130*H96	Ø158*H106	Ø182*H118	Ø230*H130
Outcut(mm)	Ø95	Ø115	Ø140	Ø160	Ø205





CE RoHS



### ■ Popular downlight(2.5inch-6inch)

Source: Epistar SMD CR182  
 Beam angle: 120°  
 Driver:110/220-240VAC 50/60Hz, Isolated driver, PF>0.5 or 0.9, 2/3years warranty



Order Model	GR-DL-7WE	GR-DL-9WE	GR-DL-12WE	GR-DL-15WE	GR-DL-18WE	GR-DL-24WE
Size(mm)	Ø108*H45	Ø118*H48	Ø138*H50	Ø180*H55	Ø180*H55	Ø195*H55
Outcut(mm)	Ø80-90	Ø90-95	Ø115-120	Ø150-169	Ø150-160	Ø160-175

### ■ Classic downlight(9inch-10inch)

Source: Epistar SMD CR180  
 Beam angle: 120°,  
 Driver:110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-12WD	GR-DL-15WD	GR-DL-18WD	GR-DL-24WD	GR-DL-30WD8	GR-DL-30WD9	GR-DL-30WD10
Size(mm)	Ø130*H45	Ø165*H60	Ø195*H62	Ø225*H62	Ø225*H62	Ø250*H62	Ø300*H100
Outcut(mm)	Ø110-105	Ø140-145	Ø170-175	Ø200-205	Ø200-205	Ø210-230	Ø250-280

### ■ Deep Economy downlight(IP22/IP44)


Source: Epistar SMD CR180  
 Beam angle: 120°, UGR<17  
 Driver:110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-7WP	GR-DL-12WP	GR-DL-15WP	GR-DL-20WP	GR-DL-24WP
Size(mm)	Ø95*H45	Ø115*H48	Ø138*H56	Ø170*H62	Ø170*H62
Outcut(mm)	Ø75	Ø95	Ø120	Ø150	Ø150

### ■ Trimless Led Downlight

Source: Osram/Bridgelux SMD CR182 100lm/w  
 Beam angle: 120°, UGR<15  
 Driver:110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-9WF	GR-DL-12WF	GR-DL-18WF	GR-DL-24WF
Size(mm)	Ø95*H45	Ø115*H48	Ø138*H56	Ø170*H62
Outcut(mm)	Ø75	Ø95	Ø120	Ø145





### ■ IP54 Waterproof downlight

Source: Osram/Epistar SMD CR182

Beam angle: 90°, UGR<15

Driver: 110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-7WW-03	GR-DL-12WW-03	GR-DL-18WW-03	GR-DL-24WW-03	GR-DL-30WW-03
Size(mm)	Ø94*H64	Ø115*H68	Ø140*H74	Ø180*H80	Ø185*H80
Outcut(mm)	Ø75	90-95	Ø120	Ø160	Ø160

### ■ Ip65 Waterproof downlight (COB/SMD)

Beam angle: 60° for COB; 120° for SMD

Source: COB/SMD optional

Driver: 110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-7WW	GR-DL-12WW	GR-DL-15WW	GR-DL-20WW	GR-DL-30WW	GR-DL-40WW
Size(mm)	Ø95*H45	Ø115*H50	Ø145*H60	Ø160*H60	Ø190*H60	Ø230*H75
Outcut(mm)	Ø75	Ø95	Ø125	Ø145	Ø170	Ø205



### ■ Adjustable IP65 Waterproof downlight

Source: Osram/Epistar COB CR192

Beam angle: 24/36°, UGR<13

Driver: 110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-7WW-02	GR-DL-9WW-02	GR-DL-12WW-02	GR-DL-15WW-02
Size(mm)	Ø72*H78	Ø72*H78	Ø92*H91	Ø92*H91
Outcut(mm)	Ø60	Ø60	Ø75	Ø75

### ■ Deep IP65 Waterproof downlight

Source: Osram/Epistar COB CR192


Beam angle: 24/36°, UGR<13

Driver: 110/220-240VAC 50/60Hz, LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-10WW-01	GR-DL-15WW-01	GR-DL-20WW-01	GR-DL-24WW-01
Size(mm)	Ø87*H72	Ø110*H82	Ø138*H100	Ø138*H100
Outcut(mm)	Ø75	Ø95	Ø120	Ø120





adjustable 24°



### Hot sale adjustable Spotlight

Beam angle: 15/24/36°  
 Source: Osram/Bridgelux COB CRI92, 100lm/w  
 Driver: 110/220-240V LiFud/Osram/Philips/Boke/Eagleries 3/5Years warranty



Order Model	GR-DL-7WG	GR-DL-10WG	GR-DL-15WG	GR-DL-20WG	GR-DL-25WG	GR-DL-30WG
Size(mm)	Ø85*H80	Ø85*H80	Ø110*H88	Ø110*H88	Ø130*H120	Ø130*H120
Outcut(mm)	Ø75	Ø75	Ø95	Ø95	Ø120	Ø120

### Top Trimless Downlight

Beam angle: 24/36°  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-7WG-01	GR-DL-10WG-01	GR-DL-12WG-01	GR-DL-15WG-01	GR-DL-20WG-01
Wattage	7W	10W	12W	15W	20W
Size(mm)	L91*H80	L116*H85	L116*100	L142*H118	L142*H118
Outcut(mm)	Ø55	Ø75	Ø75	Ø95	Ø95

### Waterproof recessed Spotlight

Beam angle: 15/24/36°  
 Source: Osram/Bridgelux COB CRI90 100-120lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-7WG-05	GR-DL-10WG-05	GR-DL-15WG-05	GR-DL-18WG-05
Wattage	7W	10W	15W	18W
Size(mm)	Ø63*H69	Ø85*H74	Ø110*H83	Ø110*H83
Outcut(mm)	Ø55	Ø75	Ø95	Ø95



### Waterproof Trimless Downlight

Beam angle: 15/24/36°  
 Source: Osram/Bridgelux COB CRI90 100-120lm/w. IP65 waterproof  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-7WG-06	GR-DL-10WG-06	GR-DL-15WG-06	GR-DL-18WG-06
Wattage	7W	10W	15W	18W
Size(mm)	L89*H69	L114*H64	L141*83	L141*H83
Outcut(mm)	Ø55	Ø75	Ø95	Ø95





### Basic Square Downlight

Beam angle: 120°  
 Source: Epistar SMD CRI80 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, only Isolated driver, 2/3years warranty

Order Model	GR-DL-7WU	GR-DL-9WU	GR-DL-12WU	GR-DL-18WU	GR-DL-24WU
Wattage	7W	9W	12W	18W	24W
Size(mm)	Ø86*H86	Ø120*H120	Ø150*H150	Ø170*H170	Ø223*223
Outcut(mm)	L75*W75	L105*W105	L135*W135	L155*155	L205*205

### Adjustable Square Downlight



Adjustable body 30°  
 Source: Epistar SMD CRI80 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DLG-10WE	GR-DLG-15WE	GR-DLG-20WE
Wattage	10W	15W	20W
Size(mm)	L125*W125	L145*W145	L185*W185
Outcut(mm)	L105*W105	L125*W125	L160*W160

### Deep Adjustable Square Downlight



Beam angle: 24/36°  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-5WV	GR-DL-7WV	GR-DL-10WV	GR-DL-15WV
Wattage	5W	7W	10W	15W
Size(mm)	W68*H70	W90*H90	W90*H90	W107*H107
Outcut(mm)	W55*L55	W75*L75	W75*L75	W95*L95

### Gimbal Square Downlight




Beam angle: 15/24/36°  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty





Order Model	GR-DLG-10WP	GR-DLG-15WP	GR-DL-20WP	GR-DLG-30WP
Wattage	10W	15W	20W	30W
Size(mm)	L90*W90	L115*W115	L140*W140	L160*W160
Outcut(mm)	L75*W75	L95*W95	L125*W125	L145*145

### Deep Square Downlight



Beam angle: 15/24/36°  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-DL-7WX	GR-DL-9WX	GR-DL-12WX
Size(mm)	Ø86*H86	Ø120*H120	Ø150*H150
Outcut(mm)	L75*W75	L105*W105	L135*W135



## Grid downlight fixture



adjustable 24°

### Gimbal double downlight



Beam angle: 15/24/36°, white/black finished optional

Source: Osram/Bridgelux COB CRI90 100lm/w

Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DLG-10WP*2	GR-DLG-15WP*2	GR-DLG-20WP*2	GR-DLG-30WP*2
Wattage	10W*2	15W*2	20W*2	30W*2
Size(mm)	L168*W90	L210*W115	L250*W140	L300*W160
Outcut(mm)	L150*W75	L185*W95	L225*W120	L275*W145


### Deep double/Triple Downlight



Beam angle: 24°; UGR<15, Black/White reflector optional


Source: Osram/Bridgelux COB CRI90 100lm/w

Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DLG-12WA*2	GR-DLG-12WA*3
Wattage	12W*2	12W*3
Size(mm)	167*85*H62	256*85*H62
Outcut(mm)	L145*W75	L240*W75

### Recessed Linear downlight



Beam angle: 24/36°

Source: Osram/Bridgelux chips CRI90 100lm/w

Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-DL-5x2WA	GR-DL-10x2WA	GR-DL-15x2WA	GR-DL-5x2WB	GR-DL-10x2WB	GR-DL-15x2WB
Wattage	9W	18W	27W	9W	18W	27W
Size(mm)	L145*45*H35	L282*45*H35	L415*45*H35	L165*W62*H38	L298*W62*H38	L430*W62*H38
Outcut(mm)	L140*W35	L275*W35	L410*W35	L158*W51	L290*W51	L420*W52

### Adjustable double/Triple downlight



Beam angle: 24/36°; white/black finished optional

Source: Osram/Bridgelux COB CRI90 100lm/w

Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DLG-10WE*2	GR-DLG-15W*2	GR-DLG-20WE*2	GR-DLG-10WE*3	GR-DLG-15W*3	GR-DLG-20WE*3
Wattage	10W*2	15W*2	20W*2	10W*3	15W*3	20W*3
Size(mm)	L225*W125	L255*W145	L330*185	L325*W130	L365*W145	L485*W185
Outcut(mm)	L75*W75	L105*W105	L135*W135	L305*W105	L345*W125	L460*160





**Classic surface downlight**



Beam angle: 15/24/36°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-10WSM	GR-DL-10SM*2	GR-DL-15WSM	GR-DL-15WSM*2	GR-DL-20WSM	GR-DL-20WSM*2
Wattage	10W	10W*2	15W	15W*2	20W	20W*2
Size(mm)	L168*W90	L210*W115	L250*W140	L300*W160	L250*W140	L300*W160

**Top surface downlight**




Beam angle: 15/24/36°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-12WSH	GR-DL-12SH*2	GR-DL-10WSH*4
Wattage	12W	12W*2	10W*4
Size(mm)	100*100*H100	200*100*H100	200*200*H100

**Surface Linear Downlight**



Beam angle: 12/24/36°, white/black finished optional  
 Source: Osram/Philips CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-DL-5WAB	GR-DL-10WAB	GR-DL-15WAB	GR-DL-20WAB	GR-DL-25WAB	GR-DL-30WAB
Wattage	5W	10W	15W	20W	25W	30W
Size(mm)	L140*37*86	L277*37*86	L405*37*86	L534*37*86	L666*37*86	L798*37*86

**Gimbal Downlight**



Beam angle: 15/24/36°  
 Source: Osram/Bridgelux COB CRI90 100-120lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty



Order Model	GR-DL-10WG-02	GR-DL-15WG-02	GR-DL-20WG-02	GR-DL-25WG-02	GR-DL-30WG-02	GR-DL-35WG-02
Size(mm)	Ø90*H100	Ø110*H135	Ø130*H135	Ø130*H135	Ø165*H170	Ø165*H170
Outcut(mm)	Ø75	Ø95	Ø115	Ø115	Ø140-145	Ø140-145



Model	Dimension	Outcut
GR-DL-5WCL100	φ25*L100mm	φ60mm
GR-DL-5WCL200	φ25*L200mm	φ60mm
GR-DL-5WCL200	φ25*L300mm	φ60mm



Model	Dimension	Outcut
GR-DL-12WP-02	φ98*H90mm	φ75mm
GR-DL-20WP-02	φ109*H107mm	φ95mm
GR-DL-30WP-02	φ134*H130mm	φ115mm



Square Trimless downlight		
Model	Dimension	Outcut
GR-DL-10WG-08	78*78*H80mm	80*80mm
GR-DL-15WG-08	78*78*H95mm	80*80mm



### Hot sale surface downlight



Beam angle: 24°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100-120lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-FM-7WA	GR-FM-12WA	GR-FM-15WA	GR-FM-20WA
Wattage	7W	12W	15W	20W
Size(mm)	Ø55*H110	Ø75*H130	Ø95*H140	Ø115*H140



### Classic surface downlight



Beam angle: 90°, white/black finished optional  
 Source: Osram/Bridgelux SMD CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-FM-10WE	GR-FM-15WE	GR-FM-20WE	GR-FM-24WE	GR-FM-30WE
Wattage	10W	15W	20W	24W	30W
Size(mm)	Ø105*H95	Ø138*H95	Ø160*H105	Ø180*H110	Ø220*H120



### Waterproof cylinder downlight



Beam angle: 40/60°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100-120lm/w  
 Driver: 110/220-240VAC 50/60Hz, isolated driver / DONE driver, 3/5years warranty

Order Model	GR-FM-10WF	GR-FM-15WF	GR-FM-20WF	GR-FM-25WF	GR-FM-30WF	GR-FM-40WF	GR-FM-50WF
Wattage	10W	15W	20W	25W	30W	40W	50W
Size(mm)	Ø75*H117	Ø95*H128	Ø95*H128	Ø120*H150	Ø120*H150	Ø147*H180	Ø171*H200

### Slim Waterproof Surface downlight



Source: Epistar SMD CRI80 100-120lm/w  
 Body: Plastic body, white/silver/gold/black frame options  
 Driver: 110/220-240VAC 50/60Hz, constant current driver, 2/3years warranty only

Order Model	GR-CD-12WE	GR-CD-18WE	GR-CD-24WE	GR-CD-30WE
Wattage	12W	18W	24W	30W
Size(mm)	Ø230*H60	Ø300*H60	Ø400*H60	Ø480*H60





### Gimbal surface downlight

Beam angle: 24/36°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-DL-10WI	GR-DL-15WI	GR-DL-20WI	GR-DL-25WI
Wattage	10W	15W	20W	25W
Size(mm)	Ø70*H100	Ø90*H110	Ø110*H115	Ø110*H130



### Fold surface downlight

Beam angle: 24°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-DL-10WZ	GR-DL-15WZ	GR-DL-20WZ	GR-DL-25WZ
Wattage	10W	15W	20W	25W
Size(mm)	Ø60*H162	Ø72*H172	Ø82*H182	Ø82*H182



### Square surface downlight

Beam angle: 15/24/36°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-FM-7WD	GR-FM-10WD	GR-FM-12WD	GR-FM-15WD	GR-FM-20WD
Wattage	7W	10W	12W	15W	20W
Size(mm)	L55*W55*H80	L75*W75*H95	L75*W75*H130	L95*W95*H140	L115*W115*H170



### Waterproof square downlight

Beam angle: 15/24/36°, white/black finished optional  
 Source: Osram/Bridgelux COB CRI90 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty


Order Model	GR-FM-10WP	GR-FM-15WP	GR-FM-20WP
Wattage	10W	15W	20W
Size(mm)	L90*W90*H140	L110*W110*H140	L145*W145*H180



### Waterproof Surface Ceiling downlight

Beam angle: 120°, white plastic body  
 Source: Epistar SMD CRI80 100-120lm/w  
 Driver: 110/220-240VAC 50/60Hz, LiFud/Eagleries/Boke/Philips driver 3/5years warranty

Order Model	GR-CD-12WH	GR-CD-15WH	GR-CD-18WH	GR-CD-24WH
Wattage	12W	15W	18W	24W
Size(mm)	Ø275*H110	Ø275*H110	Ø325*H130	Ø325*H130





Top quality  
**FORGET ABOUT MAINTENANCE**



**Top Round High bay**

Beam angle: 60/90/120°  
Source: philips SMD CRI80 120-150lm/w  
Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 5years warranty

Order Model	GR-HB-100WA	GR-HB-150WA	GR-HB-200WA	GR-HB-240WA
Wattage	100W	150W	200W	240W
Size(mm)	Ø280*176	Ø340*182	Ø400*186	Ø400*186



**Economy Round High bay**

Beam angle: 120°  
Source: Epistar SMD CRI80 120-140lm/w  
Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 2/3/5years warranty

Order Model	GR-HB-100WE	GR-HB-150WE	GR-HB-200WE	GR-HB-240WE
Wattage	100W	150W	200W	240W
Size(mm)	Ø250	Ø300	Ø345	Ø345



**160-190lm/W Round High bay**

Beam angle: 60/90/120°  
Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 3/5years warranty

Order Model	GR-HB-100WB	GR-HB-150WB	GR-HB-200WB
Wattage	100W	150W	200W
Size(mm)	Ø248*155	Ø308*165	Ø360*175



**Philips Type High bay**

Beam angle: 90°  
Source: Philips SMD CRI80 110-140lm/w  
Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL/Philips driver, 5years warranty

Order Model	GR-HB-100WF	GR-HB-150WF	GR-HB-200WF	GR-HB-240WF
Wattage	100W	150W	200W	240W
Size(mm)	Ø380	Ø420	Ø450	Ø450



**Linear Led High bay**

Beam angle: 90°  
Source: Epistar SMD CRI80 120-140lm/w  
Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 5years warranty


Order Model	GR-HB-50WL	GR-HB-100WL	GR-HB-150WL	GR-HB-200WL	GR-HB-250WL	GR-HB-300WL
Wattage	50W	100W	150W	200W	250W	300W
Size(mm)	L292*W115	L558*W115	L824*W115	L1090*W115	L1356*W115	L1622*W115






Top quality

FOCUS ON PROJECTE SOLAR LIGHT



### Project All in two solar street light




Beam angle: 70°\*140°; 5-7raining days  
 Solar panel: Mono solar panel, high effeency, lifetime more than 25years  
 Battery: LiFePO4 Li-battery, 12.8V system , MPPT controller, 2000time recycle, 3years warranty

Order Model	GR-SSL-30WE	GR-SSL-40WE	GR-SSL-50WE	GR-SSL-60WE	GR-SSL-80WE	GR-SSL-100WE	GR-SSL-120WE
Lumens	3000lm	4000lm	5000lm	6000lm	8000lm	10000lm	12000lm
Solar Panel	18V40W	18V50W	18V65W	18V80W	18V100W	18V130W	18V170W
Battery	12.8V18AH	12.8V24AH	12.8V30AH	12.8V36AH	12.8V42AH	12.8V54AH	12.8V60AH
Install height	5-6M	6-7M	7-8M	7-9M	8-9M	9-10M	10-12M



### Adjustable Project All in one solar street light




Beam angle: 70°\*140°; Moton sensor+photocell, 7raining days  
 Solar panel: Mono solar panel, high effeency, lifetime more than 25years  
 Battery: LiFePO4 Li-battery, 12.8V system , MPPT controller, 2000time recycle, 3years warranty

Order Model	GR-SSL-40WH	GR-SSL-50WH	GR-SSL-60WH	GR-SSL-80WH	GR-SSL-100WH	GR-SSL-120WH
Lumens	4000lm	5000lm	6000lm	8000lm	10000lm	12000lm
Solar Panel	18V50W	18V65W	18V70W	18V80W	18V100W	18V130W
Battery	12.8V24AH	12.8V30AH	12.8V36AH	12.8V42AH	12.8V48AH	12.8V60AH
Install height	6-7M	7-8M	7-9M	8-9M	9-10M	10-12M



### Classic All in one street light



Beam angle: 70°\*140°; Moton sensor+photocell, 7raining days  
 Solar panel: Mono solar panel, high effeency, lifetime more than 25years  
 Battery: LiFePO4 Li-battery, 12.8V system , MPPT controller, 2000time recycle, 3years warranty

Order Model	GR-SSL-30WF	GR-SSL-40WF	GR-SSL-50WF	GR-SSL-60WA	GR-SSL-80WA	GR-SSL-100WF	GR-SSL-120WF
Lumens	3000lm	4000lm	5000lm	6000lm	8000lm	10000lm	12000lm
Solar Panel	18V50W	18V65W	18V70W	18V80W	18V100W	18V130W	18V150W
Battery	12.8V24AH	12.8V30AH	12.8V36AH	12.8V42AH	12.8V48AH	12.8V60AH	12.8V66AH
Install height	5-6M	6-7M	7-8M	7-9M	8-9M	9-10M	10-12M



### All in Two Solar Floodlight

Beam angle: 120°; aluminum body+glass cover+photocell  
 LiFePO4 Li-battery, 3.2V system, 2000times recycle. 2raining day  
 Poly solar panel, high efficiency, with remote controller, 1/2year warranty

Order Model	GR-FL-40WSL	GR-FL-60WSL	GR-FL-120WSL	GR-FL-200WSL	GR-FL-300WSL	GR-FL-400WSL	GR-FL-500WSL
Wattage	40W	60W	120W	200W	300W	400W	500W
Solar Panel	6V8W	6V12W	6V15W	6V25W	6V30W	6V35W	6V40W
Battery	3.2V5AH	3.2V10AH	3.2V15AH	3.2V20AH	3.2V25AH	3.2V30AH	3.2V40AH



### New Led streetlight

Aluminum body+PC lens+ Glass cover; IP66; 70\*140°

Source: philips SMD CRI80 100-110lm/w

Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 3/5years warranty



Order Model	GR-SL-100WD	GR-SL-120WD	GR-SL-150WD	GR-SL-180WD
Wattage	100W	120W	150W	180W
Size(mm)	490x246x80	570x290x80	570x290x80	570x290x80



### Economy Led streetlight

Beam angle: 70\*140°

Source: philips SMD CRI80 120-150lm/w

Driver: 110/220-240VAC 50/60Hz, XC/DONE/constant current driver, 2/3years warranty

Order Model	GR-SL-50WK	GR-SL-100WK	GR-SL-150WK	GR-SL-200WK
Wattage	50W	100W	150W	200W
Install dia	Ø50-55	Ø60-65	Ø60-65	Ø60-65



### Cheap Adjustable Streetlight

Beam angle: 70\*140°; IP66

Source: philips SMD CRI80 100-120lm/w; PF>0.95

Driver: 110/220-240VAC 50/60Hz, Constant current driver, 2/3years warranty

Order Model	GR-SL-50WR	GR-SL-100WR	GR-SL-150WR	GR-SL-200WR
Wattage	50W	100W	150W	200W
Install dia	Ø50mm	Ø60mm	Ø60mm	Ø60-65mm



### COB LED Street light

Beam angle: 70\*140°; install dia:60-65mm

Source: philips SMD CRI80 100-120lm/w; PF>0.95

Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 2/3/5years warranty



Order Model	GR-SL-30WC	GR-SL-50WC	GR-SL-100WC	GR-SL-150WC	GR-SL-200WC	GR-SL-250WC
Wattage	30W	50W	100W	150W	200W	250W
Size(mm)	490*190*70	500*210*70	720*265*80	860*300*90	960*310*90	1000*340*90



### Economy Modular Streetlight

Beam angle: 70\*140°; install dia:60-65mm


Source: philips SMD CRI80 110-130lm/w; PF>0.95

Driver: 110/220-240VAC 50/60Hz, XC/MOSO/MEANWELL driver, 3/5years warranty



Order Model	GR-SL-50WB-02	GR-SL-100WB-02	GR-SL-150WB-02	GR-SL-200WB-02	GR-SL-250WB-02
Wattage	100W	150W	200W	240W	250W
Size(mm)	440*265*80	507*265*80	597*265*80	687*265*80	780*265*80





### Top Adjustable Led streetlight

Beam angle: 70\*140°; IP66. PF>0.95; install dia:60-65mm  
 Source: philips SMD CR180 110-140lm/w  
 Driver: 110/220-240VAC 50/60Hz,XC/MOSO/MEANWELL driver, 3/5years warranty

Order Model	GR-SL-50WH	GR-SL-100WH	GR-SL-150WH	GR-SL-200WH
Wattage	50W	100W	150W	200W
Install dia	535*210*110	605*265*110	710*265*110	760*280*110



### Modular Project streetlight

Beam angle: 70\*140°; IP66, PF>0.95  
 Source: philips SMD CR180 120-150lm/w  
 Driver: 110/220-240VAC 50/60Hz,XC/MOSO/MEANWELL driver, 3/5years warranty

Order Model	GR-SL-100WB	GR-SL-150WB	GR-SL-200WB	GR-SL-250WB	GR-SL-300WB	GR-SL-400WB
Wattage	100W	150W	200W	250W	300W	400W
Install height	6-8m	7-9m	8-10m	10-12m	12-14m	14-18m

### Philips Type Led streetlight

Beam angle: 70\*140°; IP66, PF>0.95  
 Source: philips SMD CR180 120-150lm/w  
 Driver: 110/220-240VAC 50/60Hz,Phillips/MOSO/MEANWELL driver, 5years warranty


Order Model	GR-SL-100WF	GR-SL-150WF	GR-SL-200WF	GR-SL-250WF	GR-SL-300WF
Wattage	60W/100W	150W	200W	250W	300W
Install dia	422*318*132	522*318*132	522*318*132	655*318*132	655*318*132



### Classic Led streetlight

Beam angle: 70\*140°;IP66. PF>0.95  
 Source: philips SMD CR180 110-130lm/w  
 Driver: 110/220-240VAC 50/60Hz,XC/MOSO/MEANWELL driver, 3/5years warranty

Order Model	GR-SL-30WA	GR-SL-50WA	GR-SL-100WA	GR-SL-150WA	GR-SL-200WA	GR-SL-250WA
Wattage	30W	50W	100W	150W	200W	250W
Install dia	Ø40	Ø50	Ø60-65	Ø60-65	Ø60-65	Ø60-65



### 50W/Modular Flood Light

Beam angle: 60°/90°/70°\*140°; IP66, PF>0.95

Source: philips SMD CRI80 120-150lm/w

Driver: 110/220-240VAC 50/60Hz,Phillips/MOSO/MEANWELL driver, 3/5years warranty



Order Model	GR-FL-50WM	GR-FL-100WM	GR-FL-150WM	GR-FL-200WM	GR-FL-250WM	GR-FL-300WM	GR-FL-400WM
Wattage	50W	100W	150W	200W	250W	300W	400W
Size(mm)	W75*L315	W156*L315	W237*L315	W324*L315	W399*L315	W474*L315	W324*L610



### 50W/Modular Floodlight

Beam angle: 60°/90°/75°\*145°; IP66, PF>0.95

Source: philips SMD CRI80 120-150lm/w

Driver: 110/220-240VAC 50/60Hz,Phillips/MOSO/MEANWELL driver, 5years warranty

Order Model	GR-FL-100WE	GR-FL-150WE	GR-FL-200WE	GR-FL-250WE	GR-FL-300WE	GR-FL-400WE	GR-FL-500WE
Wattage	100W	150W	200W	250W	300W	400W	500W
Size(mm)	229*370	310*370	391*370	472*370	553*370	391*626	472*626





### 250W/Modular Stadium Floodlight

Beam angle: 25/45/60/90°; IP66, PF>0.95

Source: philips SMD CRI80 130-170lm/w; Anti-glare PC lens

Driver: 110/220-240VAC 50/60Hz,Phillips/MOSO/MEANWELL driver, 5years warranty

Order Model	GR-FL-250WG	GR-FL-500WG	GR-FL-750WG	GR-FL-1000WG
Wattage	250W	500W	750W	1000W
Size(mm)	177*415*127	360*415*127	540*415*127	360*780*127




### 500W/Modular Stadium Floodlight

Beam angle: 30°/45°/60°/90°; IP66, PF>0.95

Source: philips SMD CRI80 140-180lm/w

Driver: 110/220-240VAC 50/60Hz,MOSO/MEANWELL driver, 5years warranty

Order Model	GR-FL-500WH	GR-FL-1000WH	GR-FL-1500WH
Wattage	500W	1000W	1500W
Size(mm)	640*360*220	650*650*230	650*940*220








### Outdoor LED Floodlight



Beam angle: 120°; IP66, PF>0.95  
 Source: Epistar/philips SMD CRI80 100-110lm/w  
 Driver: 110/220-240VAC 50/60Hz, Constant current/XC/DONE, 2/3/5years warranty




Order Model	GR-FL-10WA	GR-FL-20WA	GR-FL-30WA	GR-FL-50WA	GR-FL-100WA	GR-FL-150WA	GR-FL-200WA	GR-FL-300WA	GR-FL-400WA	GR-FL-500WA
Wattage	10W	20W	30W	50W	100W	150W	200W	300W	400W	500W
Size(mm)	124x110x37	146x126x37	195*165*40	230x195x56	297x250x57	355x290x57	428x328x65	500x400x65	520x365x100	625x365x100

### COB LED Floodlight



Beam angle: 120°; IP66, PF>0.95  
 Source: Epistar COB CRI70 100lm/w  
 Driver: 110/220-240VAC 50/60Hz, Constant current driver, 2/3years warranty




Order Model	GR-FL-50WA-02	GR-FL-100WA-02	GR-FL-150WA-02	GR-FL-200WA-02	GR-FL-300WA-02	GR-FL-400WA-02	GR-FL-500WA-02
Wattage	50W	100W	150W	200W	300W	400W	500W
Size(mm)	230x195x56	297x250x57	355x290x57	428x328x65	500x400x65	520x365x100	625x365x100

### LED Floodlight with Lens & Glass cover



Beam angle: 120°; IP66, PF>0.95  
 Source: philips SMD CRI80 100-110lm/w; Anti-glare PC lens  
 Driver: 110/220-240VAC 50/60Hz, XC/DONE/MOSO driver, 3/5years warranty




Order Model	GR-FL-30WA-01	GR-FL-50WA-01	GR-FL-100WA-01	GR-FL-150WA-01	GR-FL-200WA-01
Wattage	30W	50W	100W	150W	200W
Size(mm)	195*165*40	230x195x56	297x250x57	355x290x57	428x328x65

### DOB LED Floodlight



Beam angle: 90°; IP66, 90% power.  
 Source: Epistar SMD CRI80 90-100lm/w  
 Driver: 100/ 220-240VAC 50/60Hz, DOB, PF>0.9. 2years warranty

Order Model	GR-FL-30WT	GR-FL-50WT	GR-FL-100WT	GR-FL-150WT	GR-FL-200WT
Wattage	30W	50W	100W	150W	200W
Size(mm)	182*157*27	219*184*28	274*238*29	293*272*31	344*316*31



### Outdoor Wall light

Bridgelux COB, CRI90;90-100lm/W.  
Aluminum body+toughed glass, Grey finished, IP65; 30°  
Driver: 100/ 220-240VAC 50/60Hz,DONE driver. 3years warranty

Order Model	GR-BD-10WK	GR-BD-20WK	GR-BD-30WK	GR-BD-40WK
Wattage	10W	20W	30W	40W
Size(mm)	90*90	120*120	150*150	180*180



### Rectangle Wall Light

Source: Bridgelux smd CRI80, 90-100lm/W.  
Aluminum body+toughed glass cover,IP65 waterproof; 30°  
Driver: 100/ 220-240VAC 50/60Hz,isolated driver/done. 2/3years warranty

Order Model	GR-BD-20T	GR-BD-30T	GR-BD-50T
Wattage	12W	18W	24W
Size(mm)	L200*W50*H80	L300*W50*H80	L500*W50*H80



### Square Up down Wall light

Beam angle: 30°; IP65.  
Aluminum body+toughed glass cover, Grey/Black finished optional  
Driver: 100/ 220-240VAC 50/60Hz,isolated driver/done. 2/3years warranty


Order Model	GR-BD-2x7WB	GR-BD-2x10WB	GR-BD-2x20WB
Wattage	14W	20W	40W
Size(mm)	90*90*160	120*120*300	150*150*300



### Outdoor Up down Wall light

Beam angle: 30°; IP65.  
Aluminum body+toughed glass cover, Grey/Black finished optional  
Driver: 100/ 220-240VAC 50/60Hz,isolated driver/done. 2/3years warranty

Order Model	GR-BD-2x7WA	GR-BD-2x10WA	GR-BD-2x15WA	GR-BD-2x20WA
Wattage	2x7W	2x10W	2x15W	2x20W
Size(mm)	Φ90*H260	Φ108*H300	Φ108*H300	Φ145*H300



Square recessed wall light  
Output:80\*80mm, 3Watt



Rectangle wall light  
Output:205\*55mm, 3Watt



Narrow recessed wall light  
Output:170\*35mm 3Watt



### ■ Ip54 Wall Mounted Mirror Light



Source: Epistar SMD Chips, 100lm/W; CRI80  
 Stainless steel + PMMA Cover, aluminum color, IP54  
 Driver: 100/ 220-240VAC 50/60Hz, Isolated driver/DONE brand. 2/3years warranty

Order Model	GR-BD-9WM	GR-BD-12WM	GR-BD-15W
Wattage	9W	9W/12W	15W/18W
Size(mm)	90*90	600mm	900mm

### ■ Round Aluminum LED Bulkhead



Source: Epistar SMD Chips, 100lm/W; CRI80  
 Aluminum body, white/Black finished optional, IP65  
 Driver: 100/ 220-240VAC 50/60Hz, DONE driver. 2/3years warranty

Order Model	GR-BD-12WR	GR-BD-15WR	GR-BD-18WR	GR-BD-24WR
Wattage	12W	15W	18W	24W
Size(mm)	Ø225*H90	Ø275*H100	Ø275*H100	Ø275*H100

### ■ Oval Aluminium LED Bulkhead



Source: Epistar SMD Chips, 100lm/W; CRI80  
 Aluminum body, white/Black finished optional, IP65  
 Driver: 100/ 220-240VAC 50/60Hz, DONE driver. 2/3years warranty




Order Model	GR-BD-12WF	GR-BD-15WF	GR-BD-18WF
Wattage	12W	15W	18W
Size(mm)	L225*W80*H90	L275*W80*H90	L275*W80*H90

### ■ High Power Wall Pack Light



Source: Epistar SMD Chips, 110-140lm/W; CRI80  
 Aluminum body, Coffe finished, IP65  
 Driver: 100/ 220-240VAC 50/60Hz, DONE driver. 3/5years warranty

Order Model	GR-BD-50WP	GR-BD-70WP	GR-BD-100WP	GR-BD-120WP
Wattage	50W	70W	100W	120W
Size(mm)	336*216*182	336*216*182	385*247*195	385*247*195



Adjustable Up down wall light  
 GR-BD-2x3WE



Waterproof up down wall light  
 GR-BD-2x5WD Round/Square



Single head wall light  
 GR-BD-7WQ/10WQ/15WQ/20WQ






### DC24V Inground Light

input voltage: DC24V or 12V  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover+ embaded part, IP67

Order Model	GR-GL-1WB42	GR-GL-1WB52	GR-GL-1W-62B	GR-GL-3WB
Wattage	1W	1W	1W	3W
Outcut(mm)	φ38*H85	φ48*H95	φ58*H105	φ70*H105



### Side-lighting Inground light

input voltage: AC/ DC24V or 12V  
 Source: Epistar LED, 3000k-6500k/ Green/ Bluer Red optiona  
 Stainless steel frame+Aluminum body+embaded part, IP67


Order Model	GR-GL-1WB42	GR-GL-1W62B	GR-GL-1W55B	GR-GL-1W55B
Wattage	1W	1W	2W	3W
Outcut(mm)	φ38*H85	φ48*H80	φ58*H100	φ58*H105



### Project led Inground Light

input voltage:110-240VAC 50/60Hz.  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover+ embaded part, IP67;30°

Order Model	GR-GL-1WA	GR-GL-3WA	GR-GL-6WA	GR-GL-9WA	GR-GL-18WA	GR-GL-24WA	GR-GL-36WA
Wattage	1W	3W	6W	9W/12W	18W	24W	36W
Outcut(mm)	φ38*H65	φ95*H90	φ115*H95	φ140*H105	φ195*H105	φ195*H105	φ200*H105



### Square LED Inground Light

input voltage:110-240VAC 50/60Hz.  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover+ embaded part, IP67;30°

Order Model	GR-GL-4WF	GR-GL-5WF	GR-GL-6WF	GR-GL-9WF	GR-GL-12WF	GR-GL-16WF	GR-GL-24WF
Wattage	4W	5W	6W	9W	12W	16W	24W
Outcut(mm)	90*90	115*115	130*130	140*140	150*150	190*190	240*240



### Linear LED Inground light

input voltage:110-240VAC 50/60Hz.  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover+ embaded part, IP67;30°

Order Model	GR-GL-5WL	GR-GL-6WL	GR-GL-9WL	GR-GL-12WL	GR-GL-18WL	GR-GL-24WL	GR-GL-36WL
Wattage	3/5W	6W	9W	12W	18W	24W	36W
Outcut(mm)	L190*W80	L290*W85	L290*W85	L590*W85	L590*W85	L990*W85	L990*W85





### ■ Narrow beam spotlight

Beam angle: 5°; IP66.

Aluminum body+toughed glass cover, adjustable bracket.

Driver: 100/ 220-240VAC 50/60Hz,DONE driver. 3years warranty

Order Model	GR-SP-10WM
Wattage	10W
Size(mm)	φ70*120mm



### ■ Spike/Ground Spotlight

Beam angle: 30°; IP66.

Aluminum body+toughed glass cover, adjustable bracket.

Driver: 100/ 220-240VAC 50/60Hz,isolated driver/done. 2/3years warranty

Order Model	GR-SP-3WB	GR-SP-5WB	GR-SP-7WB	GR-SP-10WB	GR-SP-15WB
Wattage	3W	5W	7W	10W	15W
Size(mm)	φ42*L80mm	φ50*L90mm	φ58*L120mm	φ61*L140mm	φ75*L160mm



### ■ Outdoor Spotlight

Beam angle: 30°; IP66. Ground/spike installation optional

Aluminum body+toughed glass cover, adjustable bracket.

Driver: 100/ 220-240VAC 50/60Hz,isolated driver/done. 3years warranty

Order Model	GR-SP-10WQ	GR-SP-20WQ	GR-SP-30WQ
Wattage	10W	20W	30W
Size(mm)	φ80*H155	φ100*H155	φ120*H155



### ■ Top outdoor Spotlight

Beam angle: 30°; IP66. adjustable body

Source: Bridgelux chips,CRI80; 100lm/W. Ground/Spike installation optional

Driver: 100/ 220-240VAC 50/60Hz,DONE Driver, PF>0.9. 3/5years warranty

Order Model	GR-SP-10WH	GR-SP-20WH	GR-SP-30WH
Wattage	10W	20W	30W
Size(mm)	φ80*L130	φ80*L130	φ108*L170



### ■ Economy Tree Spotlight

Beam angle: 30°; IP66, Spike/ground installation optional

Source: Bridgelux chips,CRI80; 100lm/W.

Driver: 100/ 220-240VAC 50/60Hz, isolated driver, 2/3years warranty

Order Model	GR-SP-5WA	GR-SP-6WA	GR-SP-9WA	GR-SP-12WA	GR-SP-18WA	GR-SP-24WA	GR-SP-36WA
Wattage	5W	6W	9W	12W	18W	24W	36W
Size(mm)	φ95	φ125	φ155	φ155	φ185	φ205	φ235



### Swimming Pool Light

Input voltage: AC/DC24V or 12V; IP68  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover, Wall mounted; 2/3years warranty

Order Model	GR-UL-9WE	GR-UL-12WE	GR-UL-18WE
Wattage	9W	12W	18W
Diameter(mm)	φ230	φ230	φ295



### Ground Underwater Led Light

Input voltage: AC/DC24V or 12V; IP68  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover; 2/3years warranty

Order Model	GR-UL-6WA	GR-UL-9WA	GR-UL-12WA	GR-GL-18WA	GR-GL-24WA
Wattage	6W	9W	12W	18W	24W
Diameter(mm)	φ120*H140	φ145*H180	φ145*H180	φ175*H210	φ210*H230



### Embaded Underwater Light

Input voltage: AC/DC24V or 12V; IP68  
 Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Stainless steel frame+Aluminum body+toughed glass cover; 2/3years warranty

Order Model	GR-UL-6WB	GR-UL-9WB	GR-UL-12WB	GR-GL-18WB	GR-GL-24WB
Wattage	6W	9W	12W	18W	24W
Outcut(mm)	φ115*H95	φ145*H115	φ155*H100	φ195*H115	φ195*H115



### DC24V/12V Linear Wall Washer Light

Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Aluminum body+toughed glass, IP67. Isolated driver, 2/3years warranty

Order Model	GR-WW-18WB	GR-WW-24WB	GR-WW-36WB
Wattage	18W	24W	36W
Length(mm)	φ38*H85	φ48*H95	φ58*H105




### 110/220VAC Linear Wall washer light

Source: Epistar LED, 3000K-6500K/ Green/ Blue/ Red optional  
 Aluminum body+toughed glass, IP67. Isolated driver, 2/3years warranty

Order Model	GR-WW-9WA	GR-WW-18WA	GR-WW-24WA	GR-WW-36WA	GR-WW-48WA
Wattage	9W	18W	24W	36W	48W
Length(mm)	500	1000	1000	1000	1000





**GR-BL-A Series**

100-240VAC 50/60Hz. IP65 3Years warran

Model	Wattage	Size(mm)
GR-BL-600A	7W	Ø108*H600
GR-BL-800A	7W	Ø108*H800
GR-BL-1000A	7W	Ø108*H1000



**GR-BL-E Series**

100-240VAC 50/60Hz. IP65 3Years warranty

Model	Wattage	Size(mm)
GR-BL-300B	7W	L160*H300
GR-BL-600B	7W	L160*H600
GR-BL-800B	7W	L160*H800



**GR-BL-B Series**

100-240VAC 50/60Hz. IP65 3Years warranty

Model	Wattage	Size(mm)
GR-BL-300B	7W	Ø120*H300
GR-BL-600B	9W	Ø120*H600
GR-BL-800B	9W	Ø120*H800



**GR-BL-D Series**

100-240VAC 50/60Hz. IP65 3Years warranty

Model	Wattage	Size(mm)
GR-BL-600D	9W	Ø120*H600
GR-BL-800D	9W	Ø120*H800
GR-BL-1000D	9W	Ø120*H1000



**GR-TY-A Series**

100-240VAC 50/60Hz. IP65 3/5Years warranty

Model	Wattage	Size(mm)
GR-TY-50WA	50W	Ø380*H560
GR-TY-70WA	70W	Ø380*H560
GR-TY-150WA	100/150W	Ø380*H560



**GR-TY-B Series**

100-240VAC 50/60Hz. IP65 3/5Years warranty

Model	Wattage	Size(mm)
GR-TY-50WB	50W	Ø600*437
GR-TY-75WB	75W	Ø600*437
GR-TY-100WB	100/150W	Ø600*437



**GR-TYD Series Modern Garden Lights**

- 1.Dimension: 150mm/160mm/200mm\* Height 2.5m/3m/3.5m/4m option
- 2.Aluminum body/ 20W/30W 40W/50W
- 3.Input voltage 100/220-240VAC 50/60Hz. 3/5Years warranty



**GR-TYF Series Garden lights**

- 1.Different pattern can be customized.
- 2.Different height can be option 2.5m/3m/3.5m/4m
- 3.Aluminum body,anti-corrosion.
- 4.Power 20W 30W 50W optional.



Add:4FL, Building B, Wanda Industrial Zone, Shiyan, Baoan District, Shenzhen  
Add2: 2nd Floor, No. 6, Fu'Qi Street, Tiebian Village, Henglan Town, Zhongshan, China



+86 13570825764 (whatsapp/ wechat ID)



+86 13570825764



info@grnled.com / grnled01@gmail.com



<https://grnled.com>